

PARTY TENT 3M

Clear-span width

300 cm

Side height

229 cm

Ridge height

284 cm

Roof pitch

20°

Bay distance

300 cm

Longest component

330 cm

Minimum tent length

600 cm

Maximum tent length

No limit

Main profile

81 x 48 x 3mm - optional 94 x 48 x 3mm

Eave / corner connection

Internal eave insert

Max. allowed wind speed to DIN

50 mph windloading

0.3 kN/m²

Extension / lean-to options

Extension (max. span 300 cm and 3 bays, located anywhere, both sides)

Flooring options

Woodenfloor with timber or steel

sub-construction

Aluminium cassetefloor with plywood or full

aluminiumboards

Compactfloor



Cover

RÖDER No. 1: PVC-coated polyester textile, flame retardant to DIN 4102 B1, M2

Special design

By using compactfloor or woodenfloor with steel sub-construction and weights anchoring can be omitted

Portal beams can be used in place of cross struts



29.01.2009, www.r-zs.de/en/2

RÖDER Zelt- und Veranstaltungsservice GmbH
63654 Büdingen Fon: +49 06049 700-0
Verkauf: Am Lautenstein Fax: +49 06049 700-339
Vermietung: An den Ellern Fon: +49 06049 700-309
HRB 3261, Friedberg UST.-IdNr.: DE 112607812

Geschäftsführer:
Rüdiger Blasius
Jens Brüggemann
St.-Nr.: 020 225 62014

Bank:
WGZ Bank eG
KBC Bank DTLD AG
Fortis Bank
Duns-Nr.: 32-239-9494

IBAN BLZ Konto
DE73 400 600 00 0000 772 633
DE86 500 203 00 0000 295 086
DE15 370 106 00 1102 421 161
info@r-zs.com

SWIFT/BIC
GENO DE MS
BANV DE HB 500
GEBADE 33
www.r-zs.com